## ROSS Laboratory PowerMix (PDM) Specifications and Dimensions

## **STANDARD FEATURES:**

- Full vacuum change can design
- Air/oil hydraulic lift with two-hand operation air-powered controls for raising and lowering the mix can to and from the mixing position (80 100 psig air supply required)
- Integrated base design for mounting on table top or work bench
- Rectangular Stirrer and High Speed Disperser
- Agitator drive components and lift system are fully sheathed
- Stainless steel type 304 wetted parts with 80 grit polish
- Non-stainless steel components are finished with a durable two-part epoxy coating
- TEFC motors designed for 230/460V, 3ph, 50/60Hz
- Stainless steel type 304 gearbox with Viton sealing O-rings and lip seals on stirrer shafts
- Safety limit switch prevents operation of the mixer when the mix vessel is removed or not in the mixing position
- Vacuum hood is easily removed providing access to upper gearbox area for simple maintainence and cleaning

## **AVAILABLE OPTIONS:**

- Wetted parts of stainless steel type 316, Hastelloy or other special alloys
- Sanitary design with special seals, polishes, connections and stainless steel mixer sheathing
- Various agitators offered such as High Viscosity ("HV") Stirrer, finger type blade, auger, flight bars, chopper blade and other custom design agitators
- Sidewall and bottom scrapers with replaceable blades
- Internal pressure capability
- Explosion-proof motors, special voltages and frequencies
- · Sight/charge ports, inlet/outlet nozzles and flush tank discharge valves
- Temperature probes, pressure transducers and other batch sensors
- · Jacketed mix vessel for heating and/or cooling
- Internally-machined mix vessel for use with a Ross Discharge System
- · Carbon or stainless steel mixer bench. Common bench option for mounting of mixer and Discharge System
- · Variable frequency drives, explosion-proof operator stations and PLC recipe controls
- · Vacuum pump, heater, chiller and other auxiliary equipment

Model	Mixing Capacity	Planetary Stirrer			High Speed Disperser		Overall Height	Overall Width	Overall Length	Mix Vessel Overall	Mix Vessel Inner	Mix Vessel	Weight
		HP	Orbital RPM	Stirrer RPM	ΗP	Stirrer	<u> </u>		J. J.	Height	Diameter	Depth	
	Gallons					RPM	in	in	in	in	in	in	lbs
PDM-1/2	0.17 - 0.5	1/2	18 - 175	25 - 254	1	600 - 6,000	38	33	36	6.63	5.5	5.5	1,000
PDM-1	0.5 - 1	1	7 - 72	11 - 112	1	700 - 7,000	41	33	36	6.5	8.25	5	1,100
PDM-2	0.78 - 1.5	1	7 - 72	11 - 112	1.5	500 - 5,000	41	33	36	8	9.63	6.5	1,200
PDM-4	2.25 - 4	1.5	7 - 70	10 - 101	2	450 - 4,500	45	33	36	9.63	14	8	1,400
PDM-5	2.25 - 5	1.5	7 - 70	10 - 101	2	450 - 4,500	45	33	36	11.63	14	10	1,400



## Charles Ross & Son Company 710 Old Willets Path 631-234-0500 / 800-243-ROSS(7677)

710 Old Willets Path 631-234-0500 / 800 Hauppauge, NY 11788 sales@mixers.com USA mixers.com



